

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel Box Connectors

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined tapered male threads by machined smooth bore inside diameter
- No package qty. required

Certifications and Compliances:

Calbrite stainless steel box connectors are fabricated to UL standards.

Applications:

Used to connect a box or enclosure to the conduit coupling. It can also be used with a locknut to connect two boxes side by side, or back to back and with a locknut to connect fixture housings in continuous runs.

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Size	Part Number	Inner Diameter	Width	Length	Hex Nut Thickness	Thread Length	Weight (ea) per lb.
1/2"	S60500CH00	0.580"	1.170"	1.040"	0.260"	0.625"	0.09
3/4"	S60700CH00	0.800"	1.440"	1.075"	0.285"	0.690"	0.12
1"	S61000CH00	1.050"	1.750"	1.350"	0.340"	0.900"	0.20
1-1/4"	S61200CH00	1.390"	2.090"	1.380"	0.370"	0.940"	0.28
1-1/2"	S61500CH00	1.530"	2.350"	1.430"	0.425"	0.940"	0.41
2"	S62000CH00	2.050"	2.750"	1.600"	0.430"	1.000"	1.08
2-1/2"	S62500CH00	2.380"	3.390"	1.920"	0.500"	1.270"	1.08
3"	S63000CH00	3.000"	3.390"	1.615"	0.500"	1.050"	0.93
4"	S64000CH00	3.970"	5.000"	1.740"	0.550"	1.050"	1.57

*All dimensions are for informational purposes only *Tolerances +/- 5%*