

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Conduit Caps

#### Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined tapered male threads by machined smooth bore inside diameter
- No package qty. required



#### Certifications and Compliances:

Calbrite Stainless Steel Conduit Caps are fabricated to UL and ASTM standards

#### Applications:

To "cap" off a length of conduit, conduit nipple, elbow, or any other male threaded assembly in an electrical application.

#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Size	Part Number	A (length)	B (width)	C (thickness)	Thread Length	Weight (ea) per lb.
1/2"	S60500CA00	.890"	1.160"	.180"	.40"	0.13
3/4"	S60700CA00	.890"	1.340"	.150"	.44"	0.13
1"	S61000CA00	1.040"	1.650"	.170"	.50"	0.22
1-1/4"	S61200CA00	1.130"	2.000"	.185"	.630"	0.31
1-1/2"	S61500CA00	1.130"	2.285"	.185"	.630"	0.38
2"	S62000CA00	1.190"	2.750"	.185"	.660"	0.53
2-1/2"	S62500CA00	2.000"	3.310"	.250"	1.000"	1.42
3"	S63000CA00	1.580"	3.970"	.250"	1.000"	1.34
4"	S64000CA00	1.600"	5.000"	.250"	1.000"	2.05

*All dimensions are for informational purposes only \*Tolerances +/- 5%*